

Tablet IQ Operating Electronics



Isotec's Tablet IQ is our flagship electronics operating system for repairing Isotec Safety Entrances®. Tablet IQ has all the functionality and so much more than our venerable 3 in 1 Synergy Console, and it will reduce installation cost. Tablet IQ is another industry first for Isotec; with a multitude of IP features and benefits that include WiFi or Ethernet wired utility, greater intuitive functionality, new user friendly rich interface, video viewing, intercom communication, and wireless mobility built into one platform. Either wireless or Ethernet versions will be quoted for repairing obsolete or out dated electronic operating systems. For more information contact us at www.sales. isotecinc.com.

Call us today at 720.227.0500 or email us at sales@isotecinc.com.





STANDARD FEATURES

- Advanced Hardware
 - Better Reliability
 - Reduces Service Calls
 - Longer Life Cycle
- IP Cameras and Intercoms
 - Provides superior video and audio vs. analog
 - Cameras provide 1080p resolution with the ability to zoom in on objects without losing clarity

- Wireless Tablet Control Console
 - Mobility/Portability
 - Improved Graphics
 - Simplified User Interface
 - Cameras are onscreen at all times with the ability to show full screen
 - 9-hour Battery Life on one charge



www.lsotecSecurity.com



IQ Tablet Standard Equipment & Options

STANDARD

- (1) Synergy Tablet Console (wireless)
- (1) SSR Motherboard
- (1) Transistor PLC Assembly
- (1) Distribution Board
- (1) 12V Internal Power Supply
- (1) Maintenance Console
- (1) 8 Port Ethernet Switch
- (1) Wireless Access Point w/25' plenum cable
- (1) IP Intercom (B Zone)
- (1) Axis Mini Dome IP Camera (Inspection Tray)
- (1) Device Simulator Test Board
- (1) System override key switch on low exterior
- (1) Fire Alarm override input



Rugged Rover

OPTIONS

- (2nd) Synergy Tablet Console (wireless)
- 100' to 300' Wired package for Tablet (includes (1) USB to Ethernet adapter. Cable not included.)
- (1) 24VDC 6A Power Supply
- (1) Set of Device Cables (Needed for non-synergy systems)
- IP Intercom External Mounting Box (Needed for non-synergy systems)
- (2) Voice Prompts in external mount box (Needed for non-synergy systems)
- Mounting box for external Intranet Equipment (Switch, POE, Camera hardware. Needed if there is no 8" access panel)
- Axis Door Jamb IP Camera
- Axis Height Strip IP Camera
- Axis Mini Dome IP Camera
- Additional IP Intercom (A exterior or exit lane)
- Emergency Egress (Timer board, push buttons, reset switch and cables) Emergency Systems
- Delayed Egress Emergency Buttons (Mounted next to both doors in the egress direction. Pressing either button will release both doors after 15/30 second countdown. Local audible alert is activated. Doors will remain unlocked until reset with key.)
- System Override Out (provides contact closure when the system override feature has been activated)
- Metal Alarm Out (provides contact closure when the metal detector alarm has been activated) Door Position Contacts

Made in the U.S.A.

www.lsotecSecurity.com